


# Spinsolve ULTRA

# The homogeneity of a superconducting magnet on your bench

Ultra-high field homogeneity combined with solvent suppression allows you to resolve in few minutes analytes dissolved in protonated solvents at sub-millimolar concentrations.




# Resolving metabolites in urine at milli-molar concentrations




#### Measuring sugar content in soft drinks

The Spinsolve 80 ULTRA was used to determine the sugar type and content present in soft beverages. The high sensitivity of the system allows you to quantify with high accuracy the concentration of several components like ethanol

typically present at very low concentrations in sodas.




### Metabolites produced by S. Cereviciae during Glucose Fermentation



The Spinsolve 80 ULTRA is ideal to study biochemical processes like fermentations. The high sensitivity of the 80 MHz model makes it possible to detect metabolites produced at sub millimolar concentrations in just minutes. In this particular example, solvent suppression was combined with carbon decoupling to eliminate the carbon satellites of the NMR signals of ethanol produced during the fermentation pro-The residual water peak covers about 0.1 ppm of the spectrum, making it possible to detect metabolites very close to the solvent peak.

#### Monitoring the formation of diastereomers on-line during a HWE reaction

The Spinsolve 80 ULTRA device was used in combination with our reaction monitoring software package to follow the course of a reaction on-line and also to determine its stereochemical outcome. As an example, the well-known Horner-Wadsworth-Emmons reaction (HWE reaction) was carried out and the result is shown in the figure below. The HWE reaction was essentially developed to form the E-diastereoisomer as the reaction product in favour of the corresponding Z-counterpart.



By employing the Spinsolve 80 ULTRA system, we were able to follow the conversion of the aldehyde as starting material (red signal) and the appearances of the product signals corresponding to the newly formed C-C double bonds (green and violet signals). Moreover, we were also able to determine the E:Z ratio (79:21% in favour of E) by integrating the signals of the corresponding diastereoisomers. The coupling constants were determined to confirm our assignment (16 Hz for the E-product; 13 Hz for the Z-product).


#### **Applications**

The high homogeneity of the Spinsolve ULTRA is particularly useful for samples where the compounds to be identified and quantified are dissolved in protonated solvents such as water. Applications include:

- Reaction monitoring in the presence of protonated solvents
- qNMR for samples with important signals overlap
- · Detection of impurities and contaminants
- Quantification of sugars and alcohol in beverages
- Identification and quantification of metabolites in biofluids
- Monitoring fermentation processes in bioreactors

#### Linewidth measured in a chloroform spectrum

- No sample spinning, no spinning side bands, no requirement for compressed air
- · No reference deconvolution, only standard NMR data processing is used



#### **Spinsolve ULTRA**

- Available at 60 MHz and 80 MHz operating frequency (<sup>1</sup>H)
- Nuclei: All models measure <sup>1</sup>H and <sup>19</sup>F
   Multiple X-nuclei in one system: <sup>7</sup>Li, <sup>11</sup>B, <sup>13</sup>C, <sup>15</sup>N, <sup>29</sup>Si, <sup>31</sup>P (ask for availability of other nuclei)
- Includes a powerful multi-line solvent suppression method
- Includes carbon-decoupled proton acquisition sequences on <sup>13</sup>C models
- Linewidth specifications for all models measured on 20% chloroform in deuterated acetone:

Linewidth	Spinsolve 60 MHz	Spinsolve 80 MHz
@ 50%	< 0.2 Hz	< 0.25 Hz
@ 0.55%	< 7 Hz	< 10 Hz
@ 0.11%	< 14 Hz	< 20 Hz

The high homogeneity of the Spinsolve ULTRA is possible due to advances in the patented shimming technology used in the Magritek High Homogeneity Halbach Magnets\*
\*Patent US 8,148,988 and EP 2,144,076

# Contact us now for a quote, to request a demo, or to measure your samples

Email: sales@magritek.com

Website: www.magritek.com/contact-us

 GERMANY
 +49 241 9278 7270
 UNITED STATES
 +1 855 667 6835

 UNITED KINGDOM
 +44 7468 529 615
 NEW ZEALAND
 +64 4 477 7096

For a complete listing of our global offices and distributors visit: www.magritek.com/about-us/distributors/